

PLAFONIERE DA  
PARETE O SOFFITTO

WALL OR CEILING  
FITTINGS

# DOCKS



DOCKS reinterpreta gli apparecchi di uso e gusto navale, utilizzandone i materiali tipici come l'acciaio inossidabile AISI 316L e l'alluminio marino. Proposte nelle classiche forme con e senza griglia o con palpebra, sono ideali per l'installazione in esterni particolarmente esposti agli agenti atmosferici ed alla corrosione.

Il design classico di DOCKS, la nobiltà e la robustezza dei materiali ne fanno la lampada ideale per strutture in condizioni climatiche difficili e per ogni applicazione si presti ad un connubio di resistenza ed estetica raffinata.

DOCKS reinterprets the appliances of naval use and taste, using typical materials such as AISI 316L stainless steel and marine aluminum. Proposed in the classic shapes with and without guard or with eyelid, they are ideal for outdoor installation particularly exposed to weathering and corrosion.

The classic design of DOCKS, the nobility and the robustness of the materials make it the ideal lamp for structures in difficult climatic conditions and for each application needing a combination of resistance and refined aesthetics.

WALL OR CEILING



DOCKS  
with ring



DOCKS  
with guard



DOCKS  
with eyelid


## DOCKS

### Struttura

Diffusore in policarbonato opale IK 10 antivandalo. Guarnizioni di tenuta in silicone. Corpo in alluminio pressofuso a basso tenore di rame o inox AISI 316L. Base in alluminio pressofuso. Piattello interno reggicablaggio in Al 99,8 con ingresso cavi dal retro. Viti inox.

### Structure

IK 10 vandalproof opal polycarbonate diffuser. Silicone sealing gaskets. Body in low copper content die-cast aluminium or AISI 316L stainless steel. Die-cast aluminium base. Internal wire holder plate in Al 99,8 with cable entry from the back. Stainless steel screws.



### Materiali

Alluminio marino con viti inox, resistente finitura a doppia verniciatura: decapaggio, passivazione cromica trivalente, fondo epossidico e verniciatura con polveri poliestere. Acciaio inox AISI 316L con viti inox, maschera tornita da lastra, finitura spazzolata e satinata.

### Materials

Marine aluminium + stainless steel screws, resistant finishing with double paint coating: pickling, trivalent chromic passivation, epoxy bottom and polyester powder coating. AISI 316L stainless steel, brushed and thin satined. Stainless steel screws.



# DOCKS


Parete o soffitto / Wall or ceiling



## DOCKS CON ANELLO / WITH RING



aluminium AISI 316L stainless steel



Code			Material	Lamp	W	Lm LED	Real Lm	Optic
9104	● AN - anthracite	27K - 2700K 3K - 3000K 4K - 4000K	aluminium	LED	15	1575	600	diffuse
	● AG - aluminium grey	-		E27	75	-	-	
9060	○ BI - white	-	AISI 316L stainless steel	LED	15	1575	600	
9108	● IN - stainless steel	27K - 2700K 3K - 3000K 4K - 4000K		E27	75	-	-	
9070	-	-		-	-	-	-	

Modulo LED a tensione di rete, compatibile con dimmer a taglio di fase /  
Mains voltage LED module, compatible with most phase-cut dimmers  
E27 L max 160 mm (fornite senza lampadina / supplied without lamp)

[Su richiesta / On request](#)  
Versione dimmerabile / Dimmable version

# DOCKS


Parete o soffitto / Wall or ceiling



## DOCKS CON PALPEBRA / WITH EYELID



aluminium AISI 316L stainless steel



Code			Material	Lamp	W	Lm LED	Real Lm	Optic
9127	● AN - anthracite	27K - 2700K 3K - 3000K 4K - 4000K	aluminium	LED	15	1575	298	diffuse
	● AG - aluminium grey	-		E27	75	-	-	
9067	○ BI - white	-	AISI 316L stainless steel	LED	15	1575	298	
9138	● IN - stainless steel	27K - 2700K 3K - 3000K 4K - 4000K		E27	75	-	-	
9077	-	-		-	-	-	-	


Modulo LED a tensione di rete, compatibile con dimmer a taglio di fase /  
Mains voltage LED module, compatible with most phase-cut dimmers  
E27 L max 160 mm (fornite senza lampadina / supplied without lamp)

[Su richiesta / On request](#)  
Versione dimmerabile / Dimmable version

## DOCKS CON GRIGLIA / WITH GUARD



aluminium AISI 316L stainless steel



Code			Material	Lamp	W	Lm LED	Real Lm	Optic
9121	● AN - anthracite	27K - 2700K 3K - 3000K 4K - 4000K	aluminium	LED	15	1575	600	diffuse
	● AG - aluminium grey	-		E27	75	-	-	
9064	○ BI - white	-	AISI 316L stainless steel	LED	15	1575	600	
9133	● IN - stainless steel	27K - 2700K 3K - 3000K 4K - 4000K		E27	75	-	-	
9074	-	-		-	-	-	-	

Modulo LED a tensione di rete, compatibile con dimmer a taglio di fase /  
Mains voltage LED module, compatible with most phase-cut dimmers  
E27 L max 160 mm (fornite senza lampadina / supplied without lamp)

[Su richiesta / On request](#)  
Versione dimmerabile / Dimmable version

 **Nordic** Svensk  
**EcoEnergy** Återförsäljare  
Nordic Eco Energy AB

Tel. 070-644 28 16 - info@nordicecoenergy.se - www.nordicecoenergy.se